(19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 18 August 2005 (18.08.2005)

PCT

(10) International Publication Number WO 2005/075272 A1

(51) International Patent Classification7: B61G 5/02, 9/04

(21) International Application Number:

PCT/SE2005/000071

(22) International Filing Date: 25 January 2005 (25.01.2005)

Swedish

(26) Publication Language: English

(30) Priority Data: 4 February 2004 (04.02.2004) 0400215-0

(71) Applicant (for all designated States except US): DELL-NER COUPLERS AB [SE/SE]; Vikavägen 144, S-791 95 Falun (SE).

(72) Inventor; and

(25) Filing Language:

- (75) Inventor/Applicant (for US only): HOGBRING, Magnus [SE/SE]; Kung Magnigatan 23, S-791 62 Falun (SE).
- (74) Agent: DR. LUDWIG BRANN PATENTBYRÅ AB; P.O. Box 17192, S-104 62 Stockholm (SE).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TOWING ARRANGEMENT AND DEFORMATION TUBE IN A RAILWAY VEHICLE COUPLING



(57) Abstract: The invention relates to a towing arrangement being intended for train couplers and of the type that comprises a bar (8), which at a rear end has an axially projecting pin (10), which projects through a through hole (40) in a plate (11), which on botte sides is surrounded by shock-absorbing spring members (12), which always aim to hold the pin in a starting position in relation to the plate, and against the action of which the pin together with the bar are axially movable. According to the invention, the plate (11) is included in a mandrel (16) equipped with a cone (19), which mandrel is inserted into a deformation tube (17), more precisely into a wide, front tube section (22), which via a waist (23) transforms into a thinner, rear tube section (21), which is deformable by the mandrel (16). In a particular aspect, the invention also relates to a deformation tube as such.

